

SpillTech

5440 McGinnis Village Place

Suite 102

Alpharetta, GA 30005 Phone: 1-800-228-3877 Fax: 1-800-872-3764 www.spilltech.com

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: GranSorb - Loose Cellulose Granular Absorbent

CHEMICAL FAMILY: Cellulose

MANUFACTURER'S NAME: Kadent Grantek

Distribution Location:

SpillTech **Brookley Industrial Complex** 1627 O'Donoghue Street Mobile, AL 36615

Customer Service Telephone Number: 1-800-228-3877

Technical Information Telephone Number: 1-251-694-0102 ext.121

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENTS	PERCENT	CAS NUMBER	OSHA PEL	ACGIH TLV
Paper Fiber	47% - 53%	9004-34-6	N/A	N/A
Kaolin Clay	28% - 34%	1332-58-7	N/A	N/A
Calcium Carbonate	14% - 20%	471-34-1	N/A	N/A
Titanium Dioxide	<1%	13463-67-7	N/A	N/A

SECTION III: HAZARDS IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0 FLAMMABILITY: 1 REACTIVITY:

^{*}Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

SECTION IV: FIRST AID MEASURES

EYE CONTACT: Use eyewash, consult physician if accompanied by pain or irritation.

SKIN CONTACT: Wash with soap and water INHALATION: Remove by expiration INGESTION: Induce vomiting

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT: N/A

AUTO IGNITION: 220° C (428° F)

FLAMMABLE LIMITS: N/A

FIRE EXTINGUISHING MEDIA: Water, Foam, CO2, Dry Chemical SPECIAL FIRE FIGHTING PROCEDURES: Standard procedures for Class A fires

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION VI: ACCIDENTAL RELEASE MEASURES

No special steps to be taken if material is spilled or released.

SECTION VII: HANDLING AND STORAGE

Store in dry area. Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons.

SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: None Required

VENTILATION: use local exhaust to control possible air borne material.

PROTECTIVE GLOVES: None Required

EYE PROTECTION: Safety glasses with side shields are recommended as a good

practice for industrial safety.

OTHER PROTECTIVE EQUIPMENT (SPECIFY): None Required

SECTION IX: PHYSICAL DATA

APPEARANCE AND ODOR: Gray in color with musty odor

SPECIFIC GRAVITY:

BOILING POINT (C):

MELTING POINT (C):

SOLUBILITY IN WATER:

PERCENT VOLATILE BY VOLUME:

EVAPORATION RATE:

VAPOR PRESSURE (mm Hg):

N/A

BULK DENSITY: 38 – 46 lbs/cft.

SECTION X: TRANSPORT INFORMATION

DOT CLASSIFICATION: Non Hazardous

SECTION XI: WASTE XI DISPOSAL METHOD

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

SECTION XII: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: April 29, 2002 **UPDATED**: February 2008

PREPARED BY: SpillTech, Telephone Number: 1-800-228-3877.